

Safety Cans (Class Number 6051)

Safety cans are used for handling flammable liquids in quantities of five gallons (19 L) or less. They have pouring outlets equipped with tight-fitting caps or valves, normally closed by spring action, except when held open by hand. This prevents spillage if the can is tipped over or exposed to fire.

All safety cans have a flame arrester at the outlet and fill connections. Such screens prevent external fire from igniting vapors in the can while liquid is being poured.

Models 10307, 10317, 7225250, 7225140, 7225240..

Laboratory Can Models: 10307, 7225140, 10317, 7225240, 10326, 7210220, 10327, 7210120, 10345, 7210120, 1 gal (3.8 L); 7225250, 7225140, 7225240, 10709, 7225150, 3 gal (11.4 L); 7150250, 7150140, 7150240, 7150150, 10809Z, 7150150Z, 7150200Z, 5 gal (19 L). Hot-tin-dipped with self-closing faucet. 10709Z 3 GAL LAB W/08902 FAUCET EU, 7225150Z 2.5G/9.5L LAB RED W/902 FCT INT, 7225230Z 2.5G/9.5L IIAF YEL 1" HOSE INT.

Company Name:	Justrite Mfg. Co. LLC
Company Address:	3921 Dewitt Ave, Mattoon, Illinois 62938, USA
Company Website:	http://justritemfg.com
New/Updated Product Listing:	No
Listing Country:	United States of America
Certification Type:	FM Approved
Class of Work:	6051-FI Liq Safety Cans